




MFG. LIMITATIONS			
Maximum Width		Y	)
8'0" (XO)(	OX)		
9'0" (XOX)	(XOO)(OO	X)	
12'0"(XOX	)(XOO)(OX	<u>XO)</u>	
16'0" (OXX			
Custom Sizes Availa	ble		
Standard Height 6'8	" & 8'0"		
BASELINE PERFORMANCE		<u> </u>	
Thermal Inculation		T	
Thermal Insulation			
Inermal Insulation			
GLASS	U-Value	SHGC	
	.31	SHGC .24	
GLASS			
GLASS Low-E/Air	.31	.24	
GLASS Low-E/Air Low-E/Argon	.31 .27	.24	
GLASS Low-E/Air	.31 .27	.24	
GLASS Low-E/Air Low-E/Argon Structural Performa	.31 .27	.24 .24	
GLASS Low-E/Air Low-E/Argon Structural Performa Air Infiltration @ 25M	.31 .27 nce эн .12 с	.24 .24	
GLASS Low-E/Air Low-E/Argon Structural Performa Air Infiltration @ 25MI Water Penetration	.31 .27 nce эн .12 с	.24 .24 cfm/ft <sup>2</sup> 5.0 psf	
GLASS Low-E/Air Low-E/Argon Structural Performa Air Infiltration @ 25M	.31 .27 nce эн .12 с	.24 .24	
GLASS Low-E/Air Low-E/Argon Structural Performa Air Infiltration @ 25M Water Penetration Uniform Loads	.31 .27 nce 2н .12 с 6 +/-40	.24 .24 .24 .25 .0 psf .0 psf .0 psf	
GLASS Low-E/Air Low-E/Argon Structural Performa Air Infiltration @ 25MI Water Penetration	.31 .27 nce 2н .12 с 6 +/-40	.24 .24 .24 .25 .0 psf .0 psf .0 psf	



PD1201 FRAME HEAD AND JAMB







## PD12 New Construction - Prime


The American Window Systems<sup>™</sup> PD12Patio Door combines all of the features that you want in a door. It provides ease of operation and excellent performance.

Its welded sash and frame gives a generous expanse of glass for a greater viewing area and increased structural integrity. For enhanced energy efficiency, it has heavy-duty weather stripping around a deep pocket interlock and on the full perimeter of the door. The doors come in your choice of white, almond and clay solid vinyl, with high quality, attractive handles.

## FEATURES & BENEFITS

- Multi-Point Locking Hardware
- Welded sash. Mechanical frame
- Colors: White, Almond and Clay
- Internal weep system
- Steel adjustable tandem rollers
- Keyed lock cylinder
- Field Reversible XO OX
- Metal reinforcing
- Color matching hardware finish
- 1" OA tempered LE366/Argon standard glazing
- Dual fin-seal weatherstripping
- Exterior glazed
- Integral screen track
- Vinyl threshold cover
- AAMA approved PVC lineal certification
- NFRC simulations
- ENERGY STAR<sup>®</sup> Partner

## **COLOR OPTIONS**



## Contact us: 6201-C Dowdell Road Fort Worth, TX 76119

817-654-9050