




SOLID VINYL WINDOWS

SSH25WW SINGLE HUNG




SS2501  
FRAME




SH104  
KEEPER RAIL



SH1004  
KEEPER RAIL



SH106  
LOCK RAIL



SS1009  
BOTTOM RAIL



SS169  
EQUAL GLASS  
ADAPTOR



BV50  
GLAZING BEAD  
3/4" GLASS

**MADE IN TEXAS**

MFG. LIMITATIONS

	Width
Minimum	12"
Maximum	48"

	Height
Minimum	24"
Maximum	96"

\* Minimum width and heights are determined by process machinery capabilities.

BASELINE PERFORMANCE

NFRC Values

GLASS	U-Value	SHGC Value
Clear	.50	.68
Low-E 366-Air	.33	.23
Low-E 366-Arg	.30	.22

Structural Performance

Air Infiltration @ 25MPH	.08 cfm/ft <sup>2</sup>
Water Penetration	4.5 psf
Uniform Loads	+/- 52.5 psf

AAMA RATING: H-LC30



FEATURES & BENEFITS

- H-LC30 Performance.
- Slimline Frame
- Dual Sweep Lock. Exceeds forced entry requirements.
- 3/4" Insulated glass standard.
- Dual weather-stripping.
- Full 1 1/2" integral nail fin.
- Full span interlocking and reinforced sashes.
- 3 1/4" Double wall frame for increased rigidity and thermal performance.
- Constant force balance standard.
- Integrated straight, bay, and bow mull available.
- Optional two piece field mulling system, hurricane tested.
- Full family of Single Hung, Single Slider, 3-lite Slider, and Picture Windows.
- LowE<sup>3</sup> Glass Standard

COLOR OPTIONS

STANDARD



White



Almond



Clay

SPECIAL OPTION



Black

ASSEMBLIES

