

ARL Test Number	Number of Units	Model	IGU Inches/mm	Specimen Weight	Loading	STC Rating	OITC Rating	R _w Rating
TL6164	Single	SH25	3/4"	67 lbs	3.4 psf	28	23	28
			19	30.4 kg	16.4 kg/m ²			
TL6165	Single	SH25	25/32"	75 lbs	3.8 psf	31	26	32
			20	34 kg	18.3 kg/m ²			
TL6166	Single	SH25	27/32"	90 lbs	4.5 psf	32	27	33
			21.4	40.8 kg	22.0 kg/m ²			
TL6167A	Single	SH25	27/32"	91.0 lbs	4.6 psf	32	26	32
			21.7	41.3 kg	22.2 kg/m ²			
TL6168	Single	PW2501	1"	98.0 lbs	4.9 psf	30	25	30
			25.4	44.5 kg	23.9 kg/m ²			
TL6169	Single	PW2501	15/16"	116.0 lbs	5.8 psf	31	26	31
			24.4	52.6 kg	28.3 kg/m ²			
TL6176C	Single	SH46	27/32"	92.0 lbs	4.6 psf	32	27	33
			21.7	41.7 kg	22.5 kg/m ²			
TL6177	Single	SH46	25/32"	84 lbs	4.2 psf	32	27	32
			20	38.1 kg	20.5 kg/m ²			
TL6179A	Single	SH46 Larger Weather- stripping	27/32"	91.0 lbs	4.6 psf	33	27	33
			21.7	41.3 kg	22.2 kg/m ²			
TL6178	Two	SH25 (To exterior)	25/32"	167 lbs 75.7 kg	8.4 psf 40.8 kg/m ²	45	35	44
			20					
		SH25 (To interior)	27/32"					
			21.7					
TL6180	Two	SH25 (To exterior)	27/32"	181.0 lbs 82.1 kg	9.1 psf 44.2 kg/m ²	44	35	46
			21.4					
		SH25 (To interior)	27/32"					
			21.7					
TL6205	Two	SH25 (To exterior)	27/32"	184 lbs 83.5 kg	9.2 psf 44.9 kg/m ²	43	35	45
			21.7					
		SH25 (To interior)	27/32"					
			21.7					
TL6206	Two	SH25 (To exterior)	13/16"	159.0 lbs 72.1 kg	8.0 psf 38.8 kg/m ²	46	36	46
			20.7					
		SH25 (To interior)	29/32"					
			22.9					
TL6207	Single w/ Exterior Storm	PE2501 (Prime)	15/16"	156.0 lbs 70.8 kg	7.8 psf 38.1 kg/m ²	40	27	39