

Traditional architectural styling increases both beauty and durability.



The V46 American Series Vinyl Windows

FEATURES & BENEFITS

- HS-R30 Performance.
- Exterior bevel frame with sloped sill.
- Dual Sweep Lock. Exceeds forced entry requirements.
- ¾" OA Insulated glass standard.
- · Dual weather-stripping.
- Full 1½" integral nailfin.
- Full span interlocking and reinforced sashes.
- 2 7/8" Double wall frame for increased rigidity and thermal performance.
- Constant force balance standard.
- Integrated straight, bay and bow mull available.
- · Optional two piece field mulling system.
- Low E3 double strength glass standard

V46 American Single Hung

NFRC Values

| GLASS | U-Value | SHGC Value |
|---------------|---------|------------|
| Clear | .50 | .68 |
| Low-E 366 Air | .33 | .23 |
| Low-E 366 Arg | .30 | .22 |

Structural Performance

| Air Infiltration | @25 MPH | .14 cfm/ft |
|-------------------|---------|--------------|
| Water Penetration | | 6.0 psf |
| Uniform Loads | | +/- 60.0 psf |



V46 American Single Slider

NFRC Values

| GLASS | U-Value | SHGC Value |
|---------------|---------|------------|
| Clear | .52 | .68 |
| Low-E 366 Air | .33 | .23 |
| Low-E 366 Arg | .30 | .22 |

Structural Performance

| Air Infiltration | @25 MPH | .16 cfm/ft |
|-------------------|---------|--------------|
| Water Penetration | | 5.25 psf |
| Uniform Loads | | +/- 60.0 psf |



FEATURES & BENEFITS

- HS-R30 Performance.
- Exterior bevel frame with sloped sill.
- Dual Sweep Lock. Exceeds forced entry requirements.
- ¾" OA Insulated glass standard.
- Dual weather-stripping.
- Full 11/2" integral nailfin, optional.
- · Full span interlocking and reinforced sashes.
- 2 7/8" Double wall frame for increased rigidity and thermal performance.
- Tandem brass roller for ease of operation and durability.
- Integrated straight, bay and bow mull available.
- · Optional two piece field mulling system.
- Low E3 double strength glass standard

AmericanWindowSystems.com

V46 American Picture Window

NFRC Values

| GLASS | U-Value | SHGC Value |
|---------------|---------|------------|
| Clear | .46 | .65 |
| Low-E 366 Air | .31 | .24 |
| Low-E 366 Arg | .28 | .24 |

Structural Performance

| Air Infiltration | @25 MPH | .01 cfm/ft |
|-------------------|---------|--------------|
| Water Penetration | | 7.50 psf |
| Uniform Loads | | +/- 75.0 psf |



FEATURES & BENEFITS

- HS-R30 Performance.
- 3/4" OA Insulated glass standard.
- Full 11/2" integral nailfin optional.
- 2 7/8" Double wall frame for increased rigidity and thermal performance.
- · Integrated straight, bay and bow mull available.
- · Optional two piece field mulling system.
- · Low E3 double strength glass standard

V25 Casement & Awning Windows

FEATURES & BENEFITS

- HS-R30 Performance.
- Special sill design provides water run off and an extra weather-tight seal.
- All mitered sash designs lend pleasing lines for a beautiful appearance.
- Multi-point locking provides extra weather tightness and security.
- The beauty of a picture window with full sash that opens 90° for maximum ventilation.
- Low-E 3 double strength glass keeps your home comfortable and quiet.
- Bulb seal surrounds the sash for a tighter seal.
- Fold down crank handle is a standard option.

NFRC Values

| GLASS | U-Value | SHGC Value |
|---------------|---------|------------|
| Clear | .41 | .52 |
| Low-E 366 Air | .29 | .19 |
| Low-E 366 Arg | .26 | .19 |

Structural Performance

| Air Infiltration | @25 MPH | .01 cfm/ft |
|-------------------|---------|--------------|
| Water Penetration | | 7.5 psf |
| Uniform Loads | | +/- 75.0 psf |



TOUGH COLORS AND FINISHES THAT ENHANCE YOUR HOME'S BEAUTY

We understand that it's also important for a window frame, even it it's the most energy-efficient available, to look attractive and add style to your home.

Standard interior and exterior colors are White, Almond or Clay offering smooth clean lines to your home's design.



- The classic beveled frame styling increases both beauty and durability.
- Multi-chambered frame design provides excellent energy efficiency.
- "Colonial" window grids fit between the layers of glass so no cleaning is needed (optional).
- 3/4" OA Cardinal Low E 366 glass provides superior thermal and sound insulation.
- Dura-Seal spacer utilizes warm edge technology for increased energy savings in our glass units.
- Multi-chambered, aluminum-reinforced center bar for extra strength.
- Tilt-in lower sash for ease of cleaning.
- New construction nailing fin for easy installation in new or room additions (optional)
- · Heavy duty stainless steel balance system allows the sash to remain open in any position.

Not only does AWS have multiple window style options for homeowners, but we also have multiple window shapes to fit your needs. You can choose the color of windows and the grid patterns to fit your personal style preferences.

STYLES TO FIT YOUR HOME

V46 American, available in the following styles:



Single Hung



Single Hung with Grids



Casement



Single Slider



Horizontal Slider with Grids



Round Top



Operating Round Top



Round Top with Grids



Half Circle



Awning



Fixed Picture with Grids



Circle

Eyebrow

Trapezoid



Octagon



Half Circle with Grids





Operating Eyebrow



Fixed Eyebrow with Grids



Picture with Perimeter Grids



Triangle







6201-C Dowdell Road Fort Worth, Texas 76119 817-654-9050

